

# ROYCO® 482

## CORROSION PREVENTATIVE COMPOUND FOR RECIPROCATING AIRCRAFT ENGINES

**ROYCO® 482** is a light green rust and corrosion preventative oil commonly used to preserve aircraft internal combustion engines. The ashless anti corrosion additive package and highly refined petroleum base oils protect the engine by minimizing the effects of humidity and neutralizing the acidic components of engine oil oxidation and combustion by-products.

### APPLICATIONS

**ROYCO® 482** is normally used as a preservation grade engine oil for the internal preservation of engines or engine parts and accessories during moderate outdoor to long term indoor storage periods. This oil can also be used as a “flyaway” oil for reciprocating engines however operation of engines preserved with the diluted material should be limited to a maximum of fifty hours before oil change

The engine to be preserved should be filled to normal capacity with ROYCO® 482 and then run at idle until the engine reaches normal operating temperature (approx. 10 - 15 minutes). Upon shutdown the internal surfaces of the engine are now protected from rust and corrosion

Turbine engines using synthetic engine lubricating oils should use a Mil-C-8188 corrosion preventative concentrate. Turbine engines using lubricants compatible with mineral based fluids should use ROYCO® 483 corrosion preventative.

### FEATURES AND BENEFITS

#### Features

- Offers outstanding rust and corrosion prevention
- Ashless additive technology
- Highly refined base-oils



## APPROVALS AND SPECIFICATIONS

**ROYCO® 482** meets all requirements of and is qualified to MIL-SPEC: MIL-C-6529C Notice 2, Type II.

**ROYCO® 482** is also designated a preservative under MIL-STD-2073-1C.

## TYPICAL PROPERTIES

PROPERTIES	TEST METHOD	ROYCO® 482
API Gravity, 60/60 °F	ASTM D287	27.4
Kinematic Viscosity, cSt @ 100 °F	ASTM D445	256
Kinematic Viscosity, cSt @ 210 °F	ASTM D445	20.5
Flash Point, °F	ASTM D92	567
Density, pounds per gallon, 60°F		7.41

## PACKAGING

**ROYCO® 482** is available in 5 gallon pails and 55 gallon drums. Other package sizes may be available on special request.



This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2017 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

**North America**

+1.833.LANXESS  
customer.care@lanxess.com

**Europe, Middle East & Africa**

+44.161.875.3800  
emea.export@lanxess.com

**South & Central America**

+55.19.3522.5083  
atendimento.cliente@lanxess.com

**Asia Pacific**

+86.21.6109.6666  
Orders.apac@lanxess.com

