

# 1,2-Propanediol, 1,2-diacetate

This document provides a brief description of 1,2-Propanediol, 1,2-diacetate its uses, and the potential hazards associated with short and long term exposure. Environmental impact information for accidental releases is included. This information is general in nature and is not intended as a replacement for the safety data sheet (SDS), product label and other safe handling literature. For additional information consult the LANXESS Corporation safety data sheet.

# Identification

**Chemical Name:** 1,2-Propanediol, 1,2-diacetate

**Synonym(s):** 1,2-Propanediol, diacetate

Propane-1,2-diyl diacetate Methylethylene acetate 1,2-Diacetoxypropane

**CAS Number**: 623-84-7

Applicable LANXESS

Materials:

Please contact you LANXESS sales representative for a complete list of

products.

# **Description**

**Overview:** 1,2-Propanediol, 1,2-diacetate is a colorless liquid at room temperature..

The material is practically odorless to slight, ether-like.

**Uses:** This material, as sold by LANXESS, may be used as a crosslinking agent

for aqueous leather materials.

**Properties:** Solubility in Water: 76 g/L (20°C); soluble

**Density:** 1.058 g/cm<sup>3</sup> (20°C)

Vapor Pressure: 0.3 hPa (20°C)

Melting/Freezing Point: -70°C (-94 °F)

Last Revised: December 2018

# **Potential Human Health Effects**

# **Occupational Exposure**

Potential for occupational exposure exists during manufacture, and in unloading, storage, staging and transfer operations at facilities using the LANXESS material in the production of other products. A much lower potential for exposure exists in facilities using this substance in closed manufacturing processes by trained personnel.

# **Employee Training**

Workers handling the LANXESS manufactured material should be trained to implement proper handling procedures and to understand the potential health and physical hazards of this product. Process enclosures, local exhaust ventilation, or other engineering controls should be used to protect workers from potential airborne concentrations. When ventilation is insufficient, it is advised to wear NIOSH approved, air-purifying organic vapor respirator. In addition, it is recommended to use permeation resistant gloves, and work clothing and foot protection when handling the solid.

## **Consumer Exposure**

LANXESS Corporation does not sell 1,2-propanediol, 1,2-diacetate, nor materials containing the substance, to the general public.

#### **Short-Term Health Effects**

No known significant short-term effects.

#### **Long-Term Health Effects**

No known significant long-term effects.

# **Physical Hazards**

This material is stable under normal conditions of use. Prevent contact with oxidizing agents, acids, and bases. Heating to decomposition may release carbon monoxide, carbon dioxide, aldehydes, alcohols, and ethers.

# **Potential Environmental Impact**

This substance is readily biodegradable.

#### Conclusion

Under normal conditions of anticipated use as described in this Product Safety Assessment, and if the recommended safe use and handling procedures are followed, this material is not expected to pose a significant risk to human health or the environment.

# References

ToxPlanet, Hazardous Substance Data Bank, 1,2-Propylene Diacetate, 2018

European Chemicals Agency, Propane-1,2-diyl diacetate, December 2018

Safety Data Sheet (SDS), Aquaderm XL DI 2, LANXESS Corporation, July 2018

# **Contact Information**

LANXESS Corporation, Product Safety & Regulatory Affairs, 111 RIDC Park West Drive, Pittsburgh, PA 15275-1112, USA, Phone 1-800-526-9377 [1-800-LANXESS]

# **Notices**

# **Use and Application Information**

The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.