

Page 1 of 3

# Benzene, diethenyl-, polymer with ethenylbenzene and ethenylethylbenzene, chloromethylated, trimethylamine-quaternized

This document provides a brief description of Benzene, diethenyl-, polymer with ethenylbenzene and ethenylethylbenzene, chloromethylated, trimethylamine-quaternized, as represented by Lewatit<sup>®</sup> MonoPlus M500, its uses, and the potential hazards associated with short and long term exposure. Environmental impact information for accidental releases is included. This information is general in nature and is not intended as a replacement for the material safety data sheet (SDS), product label and other safe handling literature. For additional information consult the LANXESS Corporation safety data sheet.

# Identification

**Chemical Name:** Benzene, diethenyl-, polymer with ethenylbenzene and

ethenylethylbenzene, chloromethylated, trimethylamine-quaternized

Synonyms: Styrene resin 69011-19-4

Description

**Overview:** Lewatit<sup>®</sup> MonoPlus M500 is a light yellow solid at ambient temperatures.

The product has an amine-like odor and is sold in bead form.

Uses: Lewatit® MonoPlus M500 is an ion exchange resin sold by LANXESS for

such uses as the demineralization of water for industrial steam

generation, food demineralization, decolorization and hydrometallurgy

mining for catalysis and chemicals processing.

Properties: Solubility in Water: Insoluble in cold water

**Ignition Temperature:** >250°C (>482°F)

## **Potential Human Health Effects**

### **Occupational Exposure**

Potential for occupational exposure exists during manufacture, in unloading, storage, staging and transfer operations and while charging reaction vessels at facilities using Lewatit<sup>®</sup> MonoPlus M500 in the demineralization of water. A much lower potential for exposure exists in facilities using Lewatit<sup>®</sup> MonoPlus M500 in closed manufacturing processes by trained personnel.

# **Employee Training**

Workers handling Lewatit<sup>®</sup> MonoPlus M500 should be trained to implement proper handling procedures and to understand the potential health and physical hazards of this product. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Respirator use must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. In addition, LANXESS recommends gloves, safety glasses with side shields, suitable protective clothing and footwear be worn when handling Lewatit<sup>®</sup> MonoPlus M500.

# **Consumer Exposure**

LANXESS Corporation does not sell Lewatit® MonoPlus M500 to the general public.

## **Short-Term Health Effects**

No known significant effects or critical hazards.

# **Long-Term Health Effects**

No known significant effects or critical hazards.

# **Physical Hazards**

Lewatit<sup>®</sup> MonoPlus M500 is stable under normal conditions of use. Avoid contact with strong oxidizing agents. Heating to decomposition may release carbon monoxide, carbon dioxide and nitrogen oxides. Avoid heat, open flames and other potential sources of ignition.

# **Potential Environmental Impact**

No adverse environmental impact is expected.

#### Conclusion

Under normal conditions of anticipated use as described in this Product Safety Assessment, and if the recommended safe use and handling procedures are followed, Lewatit® MonoPlus M500 is not expected to pose a significant risk to human health or the environment.

### References

**MedlinePlus Medical Encyclopedia**, U.S. National Library of Medicine and the National Institutes of Health

Safety Data Sheet (SDS), Lewatit® MonoPlus M500, LANXESS Corporation

## **Contact Information**

LANXESS Corporation, Product Safety & Regulatory Affairs, 111 RIDC Park West Drive, Pittsburgh, PA 15275-1112, USA, Phone 1-800-526-9377 [1-800-LANXESS]

# **Notices**

## **Use and Application Information**

The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.