

# ROYCO® 44

## ANTISEIZE COMPOUND

**ROYCO® 44** is a heavy-duty anti-seize compound Graphite And Technical Petrolatum developed for use on aircraft engine spark plugs, igniters, and threaded fasteners and fittings. ROYCO® 44 has a consistency similar to modeling clay and is black in color.

### APPLICATIONS

**ROYCO® 44** is recommended for use as an anti-seize compound for threaded fasteners, fittings as well as spark plugs, igniters, and similar threaded aircraft engine accessory requiring an electrically conductive anti-seize compound or torque aid. This compound may be safely used in contact with corrosion resistant metals such as austenitic stainless steels, titanium, nickel and cobalt alloys.

### FEATURES AND BENEFITS

#### Features

- **ROYCO® 44 contains graphite; it may be safely used in contact with austenitic corrosion-resistant steels, titanium, nickel, cobalt alloys, similar corrosion-resistant metals and alloys.**

### APPROVALS & SPECIFICATIONS

**ROYCO® 44** meets SAE AMS-2518B which supersedes MIL-T-5544C.

### COMPATIBILITY

Austenitic corrosion-resistant steels, titanium, nickel, cobalt alloys, and similar corrosion-resistant metals and alloys. Not compatible with aluminum, magnesium, ferrous, zinc and cadmium alloys or plated coatings.



PROPERTIES	TEST METHOD	ROYCO® 44
Worked Penetration, mm	ASTM D937	193
Stability	Para 4.5.1	Pass
Material	Para 3.1	Conforms

### PACKAGING

**ROYCO® 44** is available in 24 x 1.75 lb cases. Other package sizes may be available on special request.

### LIMITATIONS

Graphite may promote corrosion of aluminum, magnesium, ferrous, zinc and cadmium alloys or plated coatings. As such, **ROYCO® 44** should not be used with such metals. This compound is an electrical conductor. Apply light coating to lower spark plug threads only. The compound must not come into contact with spark terminals or electrodes. Do not use in oxygen systems - explosion may result!



This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2017 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

**North America**

+1.833.LANXESS  
customer.care@lanxess.com

**Europe, Middle East & Africa**

+44.161.875.3800  
emea.export@lanxess.com

**South & Central America**

+55.19.3522.5083  
atendimento.cliente@lanxess.com

**Asia Pacific**

+86.21.6109.6666  
Orders.apac@lanxess.com

