

QUALITY LUBRICATES.



Anderol® FG S series

High performance food grade compressor oils at competitive prices. Anderol® FG S Series offers the most desirable characteristics of a premium compressor lubricant at a significantly lower price. A good choice for customers looking to take advantage of the benefits afforded from synthetic oils without increasing costs. anderol.com

X Anderol®

QUALITY WORKS.

LANXESS
Energizing Chemistry

ANDEROL®

FG S SERIES

Semi-synthetic food grade oils are formulated from synergistic blends of severely hydrotreated, hydrocracked (Group III) base oils to provide a more refined, high-quality product. These are enhanced with premium synthetic esters and proven additive technology, which help to improve viscosity, wear resistance at higher temperatures, and stress levels. Furthermore, this also increases their detergency properties, resulting in clean machinery lubrication.

Anderol® FG S Series offers some of the most desirable characteristics of a premium, fully synthetic compressor lubricant at a significantly lower price. This makes it a good choice for customers looking to take advantage of the benefits afforded from synthetic oils over mineral oils without increasing costs. Compatibility is assured with Anderol® FG S Series lubricant and there is no need for special precautions when switching from a mineral oil-based lubricant for use with paints, seals, gaskets and hoses.

■ Successful field trials have shown the oil life of ISO VG 46 and ISO VG 68 exceeds 6,000 hours

Anderol® FG S Series for Food Grade applications are available in ISO VG 32, 46, 68, 100

Anderol® FG S Series advantages over mineral oils

- Synthetic grade protection for expensive equipment
- Superb deposit and sludge control
- Excellent thermal and oxidative stability
- Good demulsibility and foaming resistance
- Excellent high/low temperature performance
- Excellent heat transfer properties
- Superb lubrication and cooling properties
- High stability even in extreme conditions
- High temperature shear stability
- Low volatility for longer life
- Operational savings
- Energy savings of up to 4 percent
- Extended lifetime (an additional 2,000 hours)
- Extended drain intervals
- Elimination of seasonal oil changes
- Energy savings of up to 4 percent
- Cooler compressors



TEST RESULTS

ANDEROL® FG S 46

Four-Ball Wear

In Four-Ball Wear tests used to evaluate the anti-wear properties of a lubricant, the Anderol® FG S 46 outperforms standard mineral oil.

The scar diameter left as a result of the test determines the ability of the lubricant to prevent wear. The smaller the scar diameter, the better the protection.

Although a Four-Ball wear test result of less than 0.5mm is generally regarded as very good, tests indicate that the Anderol® FG S 46 lubricant has a result of 0.35mm – demonstrating a very high film strength.

Volatility

The volatility of a lubricant defines its evaporative loss characteristics. The more volatile it is, the lower the temperature at which smaller hydrocarbon molecules will be driven off or evaporated. The loss of smaller hydrocarbons from the oil can increase the viscosity, especially at higher temperature application. A more volatile lubricant also means greater flammability. The oil film could break on the cylinder, resulting in wear as well as increased oil consumption.

Petri scale tests show that the percentage evaporation loss at 100°C over 22 hours is only 1.8% for Anderol® FG S 46 compared with 7.8% for standard mineral oil.

Thermal Oxidation Stability

The thermal oxidation stability P DSC test shows equally impressive results. High pressure differential scanning calorimetry is a thermal analytical method that allows for a fast and reliable determination of the thermal oxidation stability of the lubricant. The PDSC curve is used to determine the beginning of oxidative degradation. The time from the first exposure to air or oxygen, until the onset of the oxidation is called the oxidation induction time. The longer it takes until oxidation occurs the better the quality of the product.

Under test conditions of 1-4 mg, 200°C, heat rate 100°C/min., 500 psi air, the Anderol® FG S 46 clearly offers much better oxidation stability (106) versus standard mineral oil (87).

Deposit Control

Just as the service life of the lubricant is important, so too is its deposit control. Anderol® FG S 46 boasts exceptional deposit and sludge control, as well as an extremely low degree of deposit formation versus other products.

A series of petri scale tests were completed to demonstrate its performance and thermal oxidation stability. (See next page) All sample products were placed in a petri dish, heated to 220°C and monitored. After eight hours, Anderol® FG S 46 was lighter in color than its competitors, indicating its thermal stability. It also displayed no sign of sediment. Even four hours later, its color was largely unchanged while the others had darkened considerably. After 12 hours, it still did not show any polymer/deposit formation.

Test	Sample	Standard mineral oil ISO VG 46	Anderol® FG S 46
Four-Ball Wear ASTM D 4172	Average mm	0.46	0.35
Volatility	Petri @100°C % Evaporation loss	7.8	1.8
Thermal oxidation stability P DSC	Air 200°C Mins	86.7	106

TEST RESULTS

DEPOSIT FORMATION

Thermal Oxidation Stability Petri Scale at 220°C

Anderol® FG S 46

Competitor 1

Competitor 2

Competitor 3

After ½ hour



After 8 hours




Brown liquid

Dark brown viscous
with sediment

Dark brown viscous
with increased sedi-
ment

Black/brown viscous

After 12 hours



Brown liquid

Dark brown viscous
with increased sedi-
ment

Dark brown viscous
with sediment

Black very viscous
with sediments

The Anderol® FG S series proves that not only can food-grade lubricants provide excellent levels of performance but that it can be achieved with lower maintenance costs and minimal oil waste. Optimal lubrication without compromise.

Anderol® FG S series is H1 NSF Registered, awarded with Kosher and Halal certificates, and produced in an ISO 21469 certified plant.

ANDEROL® FG S SERIES

APPLICATIONS IN FOOD AND BEVERAGE PRODUCTION



Anderol® FG S Series are recommended for use in oil-flooded rotary screw compressors and centrifugal compressors.

Food processing applications

- Sorting and moving products down a process line
- Mixing products (dry food e.g. cereals)
- Peeling and cutting products (e.g. peeling onions)
- Filling pastries
- Creating packaging (blow moulding glass or plastic)
- Cleaning and filling packaging
- Cooling products (air knives to cool backed goods)



Beverage industry applications

- Fermentation process (increase oxygene level)
- Aeration (add oxygen to a liquid)
- Moving product through the pipes
- Create packaging (blow moulding and cooling)
- Cleaning and filling packaging
- Creating packaging (blow moulding glass or plastic)
- Cleaning and filling packaging
- Dispense soft drinks and beer at an even stream
- Sealing bottles
- Bottling beer





LANXESS

Energizing Chemistry

Anderol BV
Groot Egtenrayseweg 23
5928 PA Venlo
The Netherlands

www.anderol.com
info@anderol.com
+31 (0)77 396 0340

North America
+1 833 LANXESS
customer.care@lanxess.com

South & Central America
+55 19 3522 5083
atendimento.cliente@lanxess.com

Asia Pacific
+86 21 6109 6666
Orders.apac@lanxess.com

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided – especially that contained in our safety data and technical information sheets – and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

Unless specified to the contrary, the values given have been established or standardized test specimens. The figures should be regarded as guide values and not as binding minimum values. Kindly note that the results refer exclusively to the specimens tested. Under certain conditions, the test results established can be affected to a considerable extent by the processing conditions and manufacturing process.

©2021 Anderol BV

Anderol[®], LANXESS and the LANXESS logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.