

QUALITY PURIFIES.



QUALITY WORKS.

LANXESS
Energizing Chemistry

Lewatit® Ion Exchange Resins for the Recovery and Refining of Battery Metals

Lewatit® ion exchangers offer the fascinating possibility of binding specific metal ions selectively, such as lithium, copper, nickel, and cobalt that are suitable for use in batteries. Secondary constituents can also be separated, such as zinc from copper electrolytes or cobalt from nickel or copper salt solutions. In this process, the metal ions are removed from the aqueous solution and accumulated on the ion exchange resin, which greatly facilitates their further processing – or disposal, in the case of waste water flows. The use of ion exchange resins leads to highly efficient refining processes that can be used for the production of high-performance batteries with a good efficiency and water balance.

Applications and Benefits

Lewatit® ion exchange resins are crucial for many different metals processing applications. Three of most important applications and the benefits of our resins are described below.

1) Recovery of battery metals

The resin in pulp (RIP) technology is a very promising recovery approach, because battery metals can be extracted and concentrated from ore pulps, directly after leaching, without the need for CAPEX-intensive countercurrent decantation processes. To achieve high throughput within the continuous RIP process we developed our Lewatit® MonoPlus TP 209 XL. The resin shows the following benefits:

- High mechanical stability leads to savings on resin inventory
- Large bead size up to 0.9 mm allows high throughput in the metal loading cycle by efficient screening and sieving during resin-feed separation

2) Purification of battery metals

High-purity metal concentrates can be produced by the use of selective Lewatit® resins. Battery metal concentrates pass through the ion exchange resin bed, while impurities are loaded onto the resin, yielding pure concentrates that are needed for high-quality batteries. Benefits include:

- Up to two times higher cycle time compared to conventional resins allows savings on regeneration chemical costs
- Excellent exchange kinetics ensures contaminant removal down to trace levels and yields high battery metal concentrates
- High resilience of resins towards osmotic and mechanical stress results in longer lifetimes

3) Recycling

The growing demand for high purity battery lithium, nickel, cobalt and copper, requires access to new resources. The most economic and environmental friendly approach is the recycling of end of life batteries. Lewatit® ion exchange resins are crucial for many process steps in the hydro-metallurgical recycling flow sheets.

4) Waste water treatment

Waste water streams generated by battery metals processing plants, e.g., mining tailings, can be efficiently treated by Lewatit® MonoPlus TP 207. This resin selectively removes toxic heavy metals in the presence of high concentrations of other constituents of the waste water, e.g., hardness. Valuable heavy metals can additionally be recovered and recycled from the resin by selective regeneration. Benefits include:

- Up to 40% longer cycle time compared to conventional resins leads to low regeneration chemical costs
- Reliable and viable reduction of critical contaminants concentration well below required limit

Lewatit® Resins for Metal Processing Applications – Solutions for the Preparation of Critical Battery Materials

	Nickel and Cobalt						Copper				Lithium		LiPF ₆
	Recycling	Recovery Fixed Bed	Recovery Resin in Pulp	Concentrate Purification	Separation	Waste Water	Recovery Resin in Pulp	Recovery Fixed Bed	Waste Water	Concentrate Purification	Brine Purification	Recycling	Purification
Lewatit® MonoPlus TP 209 XL		■	■			■	■						
Lewatit® MonoPlus TP 207	■	■		■		■		■				■	
Lewatit® VP OC 1026	■			■									
Lewatit® TP 272				■									
Lewatit® MDS TP 220				■	■			■	■				
Lewatit® MDS TP 260	■			■		■		■		■		■	
Lewatit® MDS TP 208											■		
Lewatit® MonoPlus TP 214				■									
Lewatit® TP 308											■		
Lewatit® MP 62 WS				■									■
Lewatit® TP 108	■												
Bayoxide® E IN 30				■							■		

We will be happy to support your business. Please contact us for additional information: visit www.lewatit.com



LANXESS Deutschland GmbH
Liquid Purification Technologies
Kennedyplatz 1
50569 Cologne, Germany
Phone: +49 221 8885 0
lewatit@lanxess.com

Health and Safety Information: Appropriate literature has been assembled which provides information concerning the health and safety precautions that must be observed when handling the LANXESS products mentioned in this publication. For materials mentioned which are not LANXESS products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be followed. Before working with any of these products, you must read and become familiar with the available information on their hazards, proper use and handling. This cannot be overemphasized. Information is available in several forms, e.g., material safety data sheets, product information and product labels. Consult your LANXESS representative in Germany or contact the Regulatory Affairs and Product Safety Department of LANXESS Deutschland GmbH or – for business in the USA – the LANXESS Corporation Product Safety and Regulatory Affairs Department in Pittsburgh, PA, USA.

Regulatory Compliance Information: Some of the end uses of the products described in this publication must comply with applicable regulations, such as the FDA, BIR, NSF, USDA, and CPSC. If you have any questions on the regulatory status of these products, contact – for business in the USA – the LANXESS Corporation Regulatory Affairs and Product Safety Department in Pittsburgh, PA, USA or for business outside US the Regulatory Affairs and Product Safety Department of LANXESS Deutschland GmbH in Germany. The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

All trademarks are trademarks of the LANXESS Group, unless otherwise specified. Status 02/2024.